

JURA

XLR BALANCED STEREO CABLE



DESCRIPTION

- 24k Gold plated phosphor bronze & tellurium copper pins within metal connectors for optimum conductivity and contact strength.
- OFC-SPC -99,99% - 4N conductors (0,5 & 1,04mm²) with pure silver plated and PE insulation with a better structural integrity, optimizing the transfer of very high frequencies and the total respect of higher harmonics, an essential element for the respect of timbres.
- Triple shielding for perfect insulation against electromagnetic and radiophonic interferences (RFI & EMI): Hot pin and cold pin conductors insulated with copper-mylar foil. Central core filled in with cotton fibre to limit micro-vibrations inner, peripheral insulation in aluminum strip and thick PVC on the outside.

SPECIFICATIONS

Finish and connectics : *Matt dark grey fabric braid and Smooth texture*
Connectors : *Metal XLR male & femelle*
Outer diameter : *9,6 mm*
Available Length : *1m - 1,5m - 2m - 3m*

AVAILABLE LENGTH

1m SKU : NORJURXLR100 EAN : 3 700 795 185 131	1,5m SKU : NORJURXLR150 EAN : 3 700 795 185 148
2m SKU : NORJURXLR200 EAN : 3 700 795 185 155	3m SKU : NORJURXLR300 EAN : 3 700 795 185 162

